



DLVG-2112 Installation Instructions



Necessary tools for installation:

- | | |
|---------------------|---------------------|
| 1. Measuring tape | 4. Electrical Drill |
| 2. Ruler | 5. Screwdriver |
| 3. Inner wrench key | 6. Allen Key |

Parts list:

1.	Joint screw	16	2.	Dowel	12
3.	Cabinet	1	4.	Bottom wooden shelf	1
5.	Screw	2	6.	Towel bar	1
7.	Mounting bracket	2	8.	T-trap	1
9.	Glass countertop	1	10.	Glass basin	1
11.	Pop-up drain	1	12.	Mirror	1
13.	Mirror shelf	1	14.	Mirror stand	1

Mounting Process:

1. Find proper installation height for the vanity.
2. Secure the wall mounting brackets (#7) using dowels (#2) and joint screws (#1). Make sure they are leveled.
3. Secure the brass pads in the brackets.
4. Locate the position of the cabinet (#3) making sure it's at the same level as brackets.
5. Mark the drill holes for the cabinet. Drill the holes.
6. Fasten the bottom wooden shelf (#4) and the cabinet together.
7. Secure the cabinet with the shelf next to the brackets.
8. Place the glass countertop (#9) on the brass pads. Make sure there are plastic gaskets in between the glass and the brass pads.
9. Settle the basin (#10) with the mounting ring and washer.
10. Install the drain assembly (#8, 11). Connect trap to drain assembly. Hand tight to check alignment.
11. Secure the faucet in place. Connect hot and cold water lines.
12. Locate the desired height for the mirror (#12) and mirror stand (#14). Drill the holes. Put dowels (#2); fasten with screws (#1).
13. Fasten the small cabinet to the mirror shelf (#13).
14. Insert mirror (#12) into the mirror stand.

NOTE:

1. Avoid dinting or bumping when carrying, installing or using the glass vanity.
2. Don't scrape or scratch the glass surface or painted area.
3. Make sure the brackets are leveled and steady.
4. Do not over tighten when installing the faucet or drain assembly.
5. When securing the glass basin make sure to put mounting ring and washer.
6. Make brass pads adjustment if necessary to level the countertop.

